

POE SWITCH
MODEL : TS42100P



- Easy to use, no configuration, plug and play, flexible expansion of home, office network without power line layout restrictions.
- flexible expansion of home, office network without power line layout restrictions.
- Mini case. Adapt to rain box installation and reduce transportation costs.
- 72W high power adapts to multiple environments.

PORTS	
Ports	10x10/100Mbps self-negotiated RJ45 port
PoE Standard	IEEE802.3af/at
PoE Port	Port 1~4
Power supply	60W MAX72 W
RJ45 PoE Power Supply	Mode A positive electrode 1/2 negative electrode 3/6 (Custom power supply mode 4 / 5 V + 7 / 8 V-)
PoE port output	Maximum 15.4 W/30W
OTHERS	
Type of forwarding	Storage forwarding
Exchange capacity	1.6 G
MAC Address Table	1K, automatic learning, automatic aging
General	
Input voltage	AC 100-240V 50/60Hz
Working temperature	0°C~40°C
Storage temperature	-40°C~70°C
Working humidity	10%-90% RH does not clot
Storage humidity	5%-90% RH does not clot
Appearance Size (L*W*H)	149 *94 *28 mm
Machine weight	Product weight(0.36 Kg)
7Package specification	30SET W*D*H 443*349*200 14.8Kg
Network media	10Base-T: UTP category 3, 4, 5 cable (≤250m) 100Base-Tx: UTP category 5, 5e cable (100m)
Lightning Level	±4KV
authentication	CE FCC