



36-ch 4K NVR

MODEL : TSNVR36C12M

- Up to 36-ch IP camera inputs
- Support for buzzer alarm
- UP TO 16TB hard disk/2 SATA PORTS
- H.265+/H.265/H.264+/H.264 video formats
- Up to 16-ch @ 8MP or 36-ch @ 5MP decoding capacity

Video And Audio

IP Video Input	36-ch
HDMI Output	1-ch, 4K (3840 × 2160)/30Hz, 1920 × 1080p/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
VGA Output	1-ch, 1920 × 1080p/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
Incoming Bandwidth	80 Mbps UP to 8ch 8MP
Audio Output	1-ch, AUX (3.5mm) 1-ch HDMI

Recording

Recording Capability	16-ch 8MP ,36-ch 5MP ,36-ch 4MP/3MP/1080P/720P
Recording Resolution	8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA /720p/VGA/4CIF/DCIF/ 2CIF/CIF/QCIF

Decoding

Decoding Format	H.265+,H.265,H.264+,H.264
Synchronous Playback	1-way 8MP 4-way 4MP

Network

Network Protocol	TCP/IP, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, SMTP, NFS, iSCSI, UPnP™, HTTP
Network Interface	1, RJ-45 10/100 Mbps self-adaptive Ethernet interface

Auxiliary Interface

SATA	2 SATA interfaces
Capacity	Up to 16TB capacity for each disk
USB Interface	2 × USB 2.0

General

Power Supply	12 VDC, 4A
Consumption	≤ 3W Hard disk not included
Working Temperature	-10 to +55° C (+14 to +131° F)
Working Humidity	10 to 90 %

